NEWAGE GLASS AND ALUMINIUM PTY LTD

PRODUCT BROCHURE
ALSPEC | HIGH PERFORMANCE AWNING CASEMENT

Made to measure in Smeaton Grange NSW

ProTilt Awning Casement Window

A high performance Alspec awning and casement window with concealed multi point locking, strong acoustic ratings and an electric winder option. Made to measure in Smeaton Grange.

41 Rw	700 Pa	1500 mm	90 kg
Acoustic rating (IGU)	Water resistance	Maximum sash height	Sash weight rating

About the Window

Excellent thermal and acoustic performance. Concealed multi point locking.

Every window is built to your exact opening at our Blackmore Road workshop in Smeaton Grange. You choose the layout, glass, colour and screens, and the same team that builds it installs it.

Installed across Macarthur

Smeaton Grange · Oran Park · Gregory Hills · Harrington Park · Gledswood Hills · Narellan · Minto · Campbelltown

Key Features

- Concealed multi-point locking for security and clean lines
- Excellent thermal and acoustic performance
- Flexible hinged design, side or top hinged for enhanced airflow
- Superior weather resistance, built for harsh conditions
- Smooth operation with easy to use crank or handle mechanisms
- Various glazing options including double glazing
- **Electric winder option** for high or hard to reach windows



Awning windows alfresco Spring Farm



Office awning windows Smeaton Grange



After high performance Macarthur

Made locally
Built at our Smeaton Grange workshop, so lead times stay short.

One team
Measured, made and installed by the same people, start to finish.

Free measure
A fixed price quote after we measure your opening on site.

ProTilt Awning Casement Window Specifications

Sizes, glass, hardware and options at a glance.

NEWAGE GLASS AND ALUMINIUM PTY LTD

Technical Data

Sash Width Options	**Option 1:** 30 mm **Option 2:** 35 mm **Option 3:** 50 mm
Maximum Product Performance	**SLS:** up to 2300 Pa **ULS:** up to 5100 Pa **Water:** up to 700 Pa
Maximum Recommended Sizes	**Height:** up to 1500 mm **Width:** up to 1200 mm **Weight:** up to 90 kg **Sash SQMs:** up to 1.8
Acoustic Performance	**6.38mm Laminate:** Rw 33 dB **12.76mm Laminate:** Rw 38 dB **6.76 / 13.5 gap / 6.76 IGU:** Rw 41 dB
Thermal Performance	**Uw range SG:** 5.8 to 7.2 **SHGC range SG:** 0.26 to 0.53 **Uw range DG:** 4.2 to 5.3 **SHGC range DG:** 0.13 to 0.48
Glazing Details	**Single Glazed:** from 4 mm (30, 35, 50mm sash) **Double Glazed:** 18 to 24 mm units
Compatible Systems	Derwent Centre Pocket Framing McArthur Evo Centre Pocket Framing ecoFRAMEplus Centre Pocket Double Glazed Framing Hunter Evo Flush Glazed Framing EcoWall 225 Flush Glazed Framing

Options & Uses

Frame and hardware

- Top or side hinged
- 30, 35 or 50mm sash options
- Crank, handle or electric winder
- Powder coat or anodised finish

Glass and screens

- Double glazing from 18 to 24mm
- Laminated acoustic glass to Rw 41
- Low E coated units
- Fly and security screens


Suited to

- Homes near traffic and flight paths across Macarthur
- New builds in Spring Farm, Oran Park and Gregory Hills


Popular Configurations




Single awning
Top hinged sash



Twin awning
Two opening sashes



Fixed over awning
Fixed light above



Casement
Side hinged sash

Viewed from outside. Dashed lines point to the hinge side.

Colour Options

Pearl White | Surfmist | Ultra Silver | Woodland Grey | Monument | Satin Black

Full powder coat and anodised range available. Colours are a guide only, ask to see a physical sample.

Ready to price your opening?

Free measure and quote.
Mon to Fri 8am to 5pm, Sat 8am to 1pm.

Find us on Google Maps

0408 585 846
info@newagewindowsupplier.com.au

Specifications are based on the system manufacturer's published data and may vary with size, glass type and wind rating. Final specifications are confirmed in your written quote. Newage Glass and Aluminium P/ L, Unit 2/16 Blackmore Rd, Smeaton Grange NSW 2567.